Geotechnical Testing Journal
Index of Volume 12
1989

Number	Month of Issue	Page
1	March	1–108
2	June	109–180
3	September	181–260
4	December	261–338

A

Abraham, B. M.: *see* Jose, B. T., Sridharan, A., and Abraham, B. M.

Adsorption: A batch-type testing method for determination of adsorption of gaseous compounds on partially saturated soils (Houston, Kreamer, and Marwig), March, 3

Agar: Chemical impregnation of cohesionless soils (Schneider, Chameau, and Leonards), Sept., 204

Aggour, M. S., Taha, M. R., Tawfiq, K. S., and Amini, F.: Cohesive soil behavior under random excitation conditions, June, 135

Almeida, M. S. S.: *see* Davies, M. C. R., Almeida, M. S. S., and Parry, R. H. G.

Amini, F.: *see* Aggour, M. S., Taha, M. R., Tawfiq, K. S., and Amini, F.

Ampadu, S. and Tatsuoka, F.: An Automated stress-path control triaxial system, Sept., 238

Anayi, J. T., Boyce, J. R., and Rogers, C. D. F.: Modified Bromhead ring shear apparatus, June, 171

Arman, A.: *see* Ferrell, R. E., Jr., Arman, A., and Grosch, J. J.

Atmatzidis, D. K.: *see* Christopher, B. R., Atmatzidis, D. K., and Krizek, R. J.

Automated testing: Hollow cylinder tests on natural rock salt (Senseny, Mellegard, and Wagner), June 157

Automation: An automated stress-path control triaxial system (Ampadu and Tatsuoka), Sept., 238

B

Backfills: A large-capacity batch filling water balloon apparatus for deep in-situ density tests (Cooper and Fleming), Sept., 222

Bedding: A technique for reducing membrane penetration and bedding errors (Lo, Chu, and Lee), Dec., 311

Bica, A. V. D.: *see* Clayton, C. R. I., Khatrush, S. A., Bica, V. D., and Siddique, A.

Blaney, G. W. and O'Neill, M. W.: Dynamic lateral response of a pile group in clay, March, 22

Book Reviews:

Geotechnical Applications of Remote Sensing and Remote Data Transmission by Johnson and Pettersson (Wiesnet), March, 102

Geotechnical Instrumentation for Monitoring Field Performance by Dunnicliff (Peters), March, 101

Bowles, J. E.: Discussion of "compaction control and the index unit weight" by Steve J. Pollus, March, 98

Boyce, J. R.: *see* Anayi, J. T., Boyce, J. R., and Rogers, C. D. F.

Brittle failure: Model studies of pressuremeter testing in soft rock (Haberfield and Johnston), June, 150

C

Calibrations: The use of Hall effect semiconductors in geotechnical instrumentation (Clayton, Khatrush, Bica, and Siddique), March, 69

Campanella, R. G.: *see* Robertson, P. K., Davies, M. P., and Campanella, R. G.

Carroll, W. F.: A nonlinear one-dimensional wave analysis of a triaxial soil specimen, March, 45

Centrifuges:

Centrifuge modeling: a study of similarity (Santamarina and Goodings), June, 163

Centrifuge modeling for projectile penetration studies (Fragaszy and Taylor), Dec., 281

Studies with centrifuge vane and penetrometer apparatus in a normal gravity field (Davies, Almeida, and Parry), Sept., 195

Use of a centrifuge in geotechnical engineering education (Craig), Dec., 288

Chameau, J. -L.: *see* Schneider, H. R., Chameau, J. -L., and Leonards, G. A.

Chemical grouting: Laboratory testing of chemically grouted sand (Christopher, Atmatzidis, and Krizek), March, 109

Chemical impregnation: Chemical impregnation of cohesionless soils (Schneider, Chameau, and Leonards), Sept., 204

Christopher, B. R., Atmatzidis, D. K., and Krizek, R. J.: Laboratory Testing of Chemically Grouted Sand, June, 109

Chu, J.: *see* Lo, S.-C. R., Chu, J., and Lee, I. K.

Chung, R. M.: *see* Ladd, R. S., Dobry, R., Dutko, P., Yokel, F. Y., and Chung, R. M.

Clays:

Direct and simple shear testing of two Canadian sensitive clays (Silvestri, Karam, Tonthat, and St-Amour), March, 11

Dynamic lateral response of a pile group in clay (Blaney and O'Neill), March, 22

Log-log method for determination of preconsolidation pressure (Jose, Sridharan, and Abraham), Sept., 230

Modified Bromhead ring shear apparatus (Anayi, Boyce, and Rogers), June, 171

A procedure for determining volumetric shrinkage of an unsaturated soil (Sibley and Williams), Sept., 181

Studies with centrifuge vane and penetrometer apparatus in a normal gravity field (Davies, Almeida, and Parry), Sept., 195

Temperature effect on preconsolidation pressure (Tidfors and Sallfors), March, 93

Clayton, C. R. I., Khatrush, S. A., Bica, A. V. D., and Siddique, A.: The use of Hall effect semiconductors in geotechnical instrumentation, March, 69

Coefficient of consolidation: Graphical method for determining the coefficient of consolidation c_v from flow-pump permeability test, Dec., 302

Coefficient of volume change: Graphical method for determining the coefficient of consolidation c_v from flow-pump permeability test, Dec., 302

Cohesionless soils: Chemical impregnation of cohesionless soils (Schneider, Chameau, and Leonards), Sept., 204

Collapse: Discussion of "Determination of collapse potential of soils" by A. J. Lutenegger and R. T. Saber (Reznik), Sept., 248

Compaction:

Discussion of "compaction control and the index unit weight" by Steve J. Pollus (Bowles), March, 98

Moisture content and density of smectites (Post), Sept., 217

Cone penetrometer: Studies with centrifuge vane and penetrometer apparatus in a normal gravity field (Davies, Almeida, and Parry), Sept., 195

Consolidation:

An automated stress-path control triaxial system (Ampadu and Tatsuoka), Sept., 238

Direct and simple shear testing of two Canadian sensitive clays (Silvestri, Karam, Tonthat, and St-Amour), March, 11

Discussion of "Determination of collapse potential of soils" by A. J. Lutenegger and R. T. Saber (Reznik), Sept., 248

Horizontal and vertical swell pressures from a triaxial test: feasibility study (Johnson), March, 87

Log-log method for determination of preconsolidation pressure (Jose, Sridharan, and Abraham), Sept., 230

Cooper, M. R. and Fleming, P. R.: A Large-Capacity Batch Filling Water Balloon Apparatus for Deep In-situ Density Tests, Sept., 222

Cracking: A procedure for determining volumetric shrinkage of an unsaturated soil (Sibley and Williams), Sept., 181

Craig, W. H.: The use of a centrifuge in geotechnical engineering education, Dec., 288

Creep: Hollow cylinder tests on natural rock salt (Senseny, Mellegard, and Wagner), June, 157

Cyclic strain: Pore-water pressure buildup in clean sands because of cyclic straining (Ladd, Dobry, Dutko, Yokel, and Chung), March, 77

D

Damping: Cohesive soil behavior under random excitation conditions (Aggour, Taha, Tawfiq, and Amini), June, 135
Davies, M. C. R., Almeida, M. S. S., and Parry, R. H. G.: Studies with Centrifuge Vane and Penetrometer Apparatus in a Normal Gravity Field, Sept., 195
Davies, M. P.: *see* Robertson, P. K., Davies, M. P., and Campanella, R. G.
Deformation: Measurements of normal deformations in joints during shear using inductance devices (Fishman and Desai), Dec., 297
Density: A large-capacity batch filling water balloon apparatus for deep in-situ density tests (Cooper and Fleming), Sept., 222
Desai, C. S.: *see* Fishman, K. L. and Desai, C. S.
Desaturation: A procedure for determining volumetric shrinkage of an unsaturated soil (Sibley and Williams), Sept., 181
Dilatancy: Design of laterally loaded driven piles using a flat dilatometer (Robertson, Davies, and Campanella), March, 30
Dobry, R.: *see* Ladd, R. S., Dobry, R., Dutko, P., Yokel, F. Y., and Chung, R. M.
Dragdown: The influence of the shape of a pile shoe on a model pile penetrating layered soil (Rowlands), Dec., 317
Dutko, P.: *see* Ladd, R. S., Dobry, R., Dutko, P., Yokel, F. Y., and Chung, R. M.
Dynamic response: Dynamic behavior of the bumpy road shaking table system (Lee and Schofield), June, 126

E

Earthquakes:
Dynamic behavior of the bumpy road shaking table system (Lee and Schofield), June, 126
Pore-water pressure buildup in clean sands because of cyclic straining (Ladd, Dobry, Dutko, Yokel, and Chung), March, 77
Education: Use of a centrifuge in geotechnical engineering education (Craig), Dec., 288
Error: A technique for reducing membrane penetration and bedding errors (Lo, Chu, and Lee), Dec., 311

F

Ferrell, R. E., Jr., Arman, A., and Grosch, J. J.: X-ray radiographic investigation of perchloroethylene migration at the Livingston derailment site, June, 119
Fishman, K. L. and Desai, C. S.: Measurements of normal deformations in joints during shear using inductance devices, Dec., 297
Fleming, P. R.: *see* Cooper, M. R. and Fleming, P. R.
Fragaszy, R. J. and Taylor, T.: Centrifuge modeling for projectile penetration studies, Dec., 281
Fredlund, D. G. and D. K. H. Wong: Calibration of Thermal Conductivity Sensors for Measuring Soil Suction, Sept., 188
Fourier analysis:
Dynamic behavior of the bumpy road shaking table system (Lee and Schofield), June, 126
Dynamic lateral response of a pile group in clay (Blaney and O'Neill), March, 22

G-H

Geogrid reinforcement: Enhancement of the uplift capacity of buried pipelines by the use of geogrids (Selvadurai), Sept., 211
Gill, J. D.: *see* Morin, R. H., Olsen, H. W., Nelson, K. R., and Gill, J. D.
Goodings, D. J.: *see* Santamarina, J. C. and Goodings, D. J.
Grosch, J. J.: *see* Ferrell, R. E., Jr., Arman, A., and Grosch, J. J.
Haberfield, C. M. and Johnston, I. W.: Model studies of pressuremeter testing in soft rock, June, 150
Hardin, B.: Effect of rigid boundaries on measurement of particle concentration, June, 143
Hazardous waste containment: A batch-type testing method for determination of adsorption of gaseous compounds on partially saturated soils (Houston, Kreamer, Marwig) March, 3
Hird, C. C. and Yang, P. C. Y.: The use of proximity transducers for local strain measurements in triaxial tests, Dec. 292
Holtz, R. D.: *see* Prapaharan, S. Holtz, R. D., and Luna J. D.
Houston, S. L., Kreamer, D. K., and Marwig, R.: A batch-type testing method for determination of adsorption of gaseous compounds on partially saturated soils, March, 3
Howard, A. K.: Minimum test specimen mass for moisture content determination, March, 39

I-J

Index unit weight: Discussion of "compaction control and the index unit weight" by Steve J. Pollus (Bowles), March, 98
In-situ testing: Discussion of "Effects of Borehole fluid on standard penetration test results" by R. B. Seed, L. F. Harder, Jr., and T. L. Youd (Schmertmann), Sept., 250
Interfaces: Measurements of normal deformations in joints during shear using inductance devices (Fishman and Desai), Dec., 297
Johnson, L. D.: Horizontal and vertical swell pressures from a triaxial test: feasibility study, March, 87
Johnston, I. W.: *see* Haberfield, C. M. and Johnston, I. W.
Joints: Measurement of normal deformations in joints during shear using inductance devices (Fishman and Desai), Dec., 297
Jose, B. T., Sridharan, A., and Abraham, B. M.: Log-log method for determination of preconsolidation pressure, Sept., 230

K

Karam, G.: *see* Silvestri, V., Karam, G., Tonthat, A., and St-Amour, Y.
Khatrush, S. A.: *see* Clayton, C. R. I., Khatrush, S. A., Bica, A. V. D., and Siddique, A.
Kolymbas, D. and Wei W.: A device for lateral strain measurement in triaxial tests with unsaturated specimens, Sept., 227
Kramer, S. L. and Sivaneswaran, N.: A nondestructive, specimen- specific method for measurement of membrane penetration in the triaxial test, March, 50
Kreamer, D. K.: *see* Houston, S. L., Kreamer, D. K., and Marwig, R.
Krizek, R. J.: *see* Christopher, B. R., Atmatzidis, D. K., and Krizek, R. J.

L

Laboratory tests: Discussion on "automatic volume change and pressure measurement devices for triaxial testing of soils" by Poul V. Lade (Tatsuoka), Dec., 323
Ladd, R. S., Dobry, R., Dutko, P., Yokel, F. Y., and Chung, R. M.: Pore-water pressure buildup in clean sands because of cyclic straining, March, 77
Lade, P.: Closure to discussion on triaxial testing by Tatsuoka and Oswell et al.
Lateral forces: Design of laterally loaded driven piles using a flat dilatometer (Robertson, Davies, and Campanella), March, 30
Lee, F. -H. and Schofield, A. N.: Dynamic behavior of the bumpy road shaking table system, June, 126
Lee, I. K.: *see* Lo, S.-C. R., Chu, J., and Lee, I. K.
Leonards, G. A.: *see* Schneider, H. R., Chameau, J. -L., and Leonards, G. A.
Liquefaction: Discussion of "Effects of Borehole fluid on standard penetration test results" by R. B. Seed, L. F. Harder, Jr., and T. L. Youd (Schmertmann), Sept., 250
Livingston derailment site: X-ray radiographic investigation of perchloroethylene migration at the Livingston derailment site (Ferrell, Arman, and Grosch), June, 119
Lo, S.-C. R., Chu, J., and Lee, I. K.: A technique for reducing membrane penetration and bedding errors, Dec., 311
Luna, J. D.: *see* Prapaharan, Holtz, R. D., and Luna, J. D.

M

Marwig, R.: *see* Houston, S. L., Kreamer, D. K., and Marwig, R.
Matric suction: Calibration of thermal conductivity sensors for measuring soil suction (Fredlund and Wong), Sept., 188
Mellegard, K. D.: *see* Senseny, P. E., Mellegard, K. D., and Wagner, L. A.
Membrane: A nondestructive, specimen-specific method for measurement of membrane penetration in the triaxial test (Kramer and Sivaneswaran), March, 50
Membrane penetration: A technique for reducing membrane penetration and bedding errors (Lo, Chu, and Lee), Dec., 311
Mercury intrusion technique: Pore size distribution of nonwoven geotextiles (Prapaharan, Holtz, and Luna), Dec. 261
Metastable soils: Discussion of "Determination of collapse of soils" by A. J. Lutenegger and R. T. Saber (Reznik), Sept., 248

Models:
Centrifuge modeling: a study of similarity (Santamarina and Goodings), June, 163
A model study of the influence of stress on the thermal conductivity of dry sand (Wetzel and Rolle), June, 167
Moisture content: Minimum test specimen mass for moisture content determination (Howard), March, 39
Moisture determination: Moisture content and density of smectites (Post), Sept., 217
Morin, R. H., Olsen, H. W., Nelson, K. R., and Gill, J. D.: Graphical method for determining the coefficient of consolidation c_v from flow-pump permeability test, Dec., 302

N-O

Nelson, K. R.: *see* Morin, R. M., Olsen, H. W., Nelson, K. R., and Gill, J. D.
Nonwoven geotextiles: Pore size distribution of nonwoven geotextiles (Prapaharan, Holtz, and Luna), Dec. 261
Oedometer test: Temperature effect on preconsolidation pressure (Tidfors and Sallfors), March, 93
O'Neill, M. W.: *see* Blaney, G. W. and O'Neill, M. W.
Olsen, H. W.: *see* Morin, R. H., Olsen, H. W., Nelson, K. R., and Gill, J. D.

P

Parry, R. H. G.: *see* Davies, M. C. R., Almeida, M. S. S., and Parry, R. H. G.
Particulate theory: Effect of ridig boundaries on measurement of particle concentration (Hardin), June, 143
Penetration:
Centrifuge modeling for projectile penetration studies (Fragaszy and Taylor), Dec., 281
A nondestructive, specimen-specific method for measurement of membrane penetration in the triaxial test (Kramer and Sivaneswaran), March, 50
Penetration resistance: The vane cone: a new device for soil shear strength measurement (Youssef), March, 60
Penetrator: Centrifuge modeling for projectile penetration studies (Fragaszy and Taylor), Dec., 281
Permeability: Graphical method for determining the coefficient of consolidation c_v from flow-pump permeability test (Morin, Olsen, Nelson, and Gill), Dec., 302
Peters, J. F.: *Geotechnical instrumentation for Monitoring Field Performance* by Dunnicliff, March, 101
Piles:
Design of laterally loaded driven piles using a flat dilatometer (Robertson, Davies, and Campanella), March, 30
Dynamic lateral response of a pile group in clay (Blaney and O'Neill), March, 22
The influence of the shape of a pile shoe on a model pile penetrating layered soil (Rowlands), Dec., 317
Pile shoe: The influence of the shape of a pile shoe on a model pile penetrating layered soil (Rowlands), Dec., 317
Pipelines: Enhancement of the uplift capacity of buried pipelines by the use of geogrids (Selvadurai), Sept., 211
Pore size distribution: Pore size distribution of nonwoven geotextiles (Prapaharan, Holtz, and Luna), Dec., 261
Post, J. L.: Moisture content and density of smectites, Sept., 217
Pradhan, T. B. S.: *see* Tatsuoka, F., Pradhan, T. B. S., and Yoshi-ie, H.
Prapaharan, S., Holtz, R. D., and Luna, J. D.: Pore size distribution of nonwoven geotextiles, Dec., 261
Preconsolidation pressure: Log-log method for determination of preconsolidation pressure (Jose, Sridharan, and Abraham), Sept., 230
Pressuremeter tests: Model studies of pressuremeter testing in soft rock (Haberfield and Johnston), June, 150
Pulse shapes: Pulse shapes from ground penetrating radar (Reames), Sept., 244

R

Radar: Pulse shapes from ground penetrating radar (Reames), Sept., 244
Reames, F. M.: Pulse shapes from ground penetrating radar, Sept., 244
Relative density: Discussion of "compaction control and the index unit weight" by Steve J. Pollus (Bowles), March, 98
Residual strength: Modified Bromhead ring shear apparatus (Anayi, Boyce, and Rogers), June, 171
Reznik, Y. M.: Discussion of "Determination of collapse potential of soils," by A. J. Lutenegger and R. T. Saber, Sept., 248
Robertson, P. K., Davies, M. P., and Campanella, R. G.: Design of laterally loaded driven piles using the flat dilatometer March, 30
Rock salt: Hollow cylinder tests on natural rock salt (Senseny, Mellegard, and Wagner), June, 157
Rocks: Model studies of pressuremeter testing in soft rock (Haberfield and Johnston), June, 150
Rogers, C. D. F.: *see* Anayi, J. T., Boyce, J. R., and Rogers, C. D. F.
Rolle, K. C.: *see* Wetzel, R. A. and Rolle, K. C.
Rowlands, G. O.: The influence of the shape of a pile shoe on a model pile penetrating layered soil, Dec., 317

S

Sallfors, G.: *see* Tidfors, M. and Sallfors, G.
Sands:
A cyclic undrained simple shear testing method for soils (Tatsuoka, Pradhan, and Yoshi-iu), Dec., 269
Laboratory testing of chemically grouted sand (Christopher, Atmatzidis, and Krizek), June, 109
A model study of the influence of stress on the thermal conductivity of dry sand (Wetzel and Rolle), June, 167
Pore-water pressure buildup in clean sands because of Cyclic straining (Ladd, Dobry, Dutko, Yokel, and Chung), March, 77
Santamarina, J. C. and Goodings, D. J.: Centrifuge modeling: a study of similarity, June 163
Saturated soil: A batch-type testing method for determination of adsorption of gaseous compounds on partially saturated soils (Houston, Kreamer, and Marwig), March, 3
Scanning electron microscopy: X-ray radiographic investigation of perchloroethylene migration at the Livingston derailment site (Ferrell, Arman, and Grosch), June, 119
Schmertmann, J. H.: Discussion of "Effects of Borehole fluid on standard penetration test" by R. B. Seed, L. F. Harder, Jr., and T. L. Youd, Sept., 250
Schneider, H. R., Chameau, J. -L., and Leonards, G. A.: Chemical impregnation of cohesionless soils, Sept., 204
Schofield, A. N.: *see* Lee, F. -H. and Schofield, A. N.
Selvadurai, A. P. S.: Enhancement of the uplift capacity of buried pipelines by the use of geogrids, Sept., 211
Semiconductors: The use of Hall effect semiconductors in geotechnical instrumentation (Clayton, Khatrush, Bica, and Siddique), March, 69
Senseny, P. E., Mellegard, K. D., and Wagner, L. A.: Hollow cylinder tests on natural rock salt, June, 157
Shear tests:
Cohesive soil behavior under random excitation conditions (Aggour, Taha, Tawfiq, and Amini), June, 135
A cyclic undrained simple shear testing method for soils (Tatsuoka, Pradhan, and Yoshi-ie), Dec., 269
Direct and simple shear testing of two Canadian sensitive clays (Silvestri, Karam, Tonthat, and St-Amour), March, 11
Modified Bromhead ring shear apparatus (Anayi, Boyce, and Rogers), June, 171
Sibley, J. W. and Williams, D. J.: A procedure for determining volumetric shrinkage of an unsaturated soil, Sept., 181
Siddique, A.: *see* Clayton, C. R. I., Khatrush, S. A., Bica, A. V. D., and Siddique, A.
Silvestri, V., Karam, G., Tonthat, A., and St-Amour, Y.: Direct and simple shear testing of two Canadian sensitive clays, March, 3
Sivaneswaran, N.: *see* Kramer, S. L. and Sivaneswaran, N.
Soil dynamics:
A nonlinear one-dimensional wave analysis of a triaxial soil specimen (Carroll), March, 45
Cohesive soil behavior under random excitation conditions, (Aggour, Taha, Tawfiq, and Amini), June, 135
Soil moisture: Minimum test specimen mass for moisture content determination (Howard), March, 39
Soil suction: Calibration of thermal conductivity sensors for measuring soil suction (Fredlund and Wong), Sept., 188
Soil tests:
Discussion on "automatic volume change and pressure measurement devices for triaxial testing of soils" by Poul V. Lade (Tatsuoka), Dec., 323
The use of proximity transducers for local strain measurements in triaxial tests (Hird and Yang), Dec., 292
Specific gravity tests: Moisture content and density of smectites (Post), Sept., 217

Sridharan, A.: *see* Jose, B. T., Sridharan, A., and Abraham, B. M.
St-Amour, Y.: *see* Silvestri, V., Karam, G., Tonthat, A., and St-Amour, Y.
Standard penetration test: Discussion of "Effect of Borehole fluid on standard penetration test results," by R. B. Seed, L. F. Harder, Jr., and T. L. Youd (Schmertmann), Sept., 250
Strain measurement:
A device for lateral strain measurement in triaxial tests with unsaturated specimens (Kolymbas and Wu), Sept., 227
The use of proximity transducers for local strain measurements in triaxial tests (Hird and Yang), Dec. 292
Stress paths:
An automated stress-path control triaxial system (Ampadu and Tatsuoka), Sept., 238
Centrifuge modeling: a study of similarity (Santamarina and Goodings), June, 163
Swell pressure: Horizontal and vertical swell pressures from a triaxial test: feasibility study (Johnson), March, 87

T

Taha, M. R.: *see* Aggour, M. S., Taha, M. R., Tawfiq, K. S., and Amini, F.
Tatsuoka, F.: *see* Ampadu, S. and Tatsuoka, F.
Tatsuoka, F., Pradhan, T. B. S., and Yoshi-ie, H.: A cyclic undrained simple shear testing method for soils (Tatsuoka, Pradhan, and Yoshi-ie), Dec., 269
Tawfiq, K. S.: *see* Aggour, M. S., Taha, M. R., Tawfiq, K. S., and Amini, F.
Taylor, T.: *see* Fragaszy, R. J. and Taylor, T.
Temperature: Temperature effect on preconsolidation pressure (Tidfors and Sallfors), March, 93
Testing errors: Effect of rigid boundaries on measurement of particle concentration (Hardin), June, 143
Test procedures: Minimum test specimen mass for moisture content determination (Howard), March, 39
Thermal conductivity:
A model study of the influence of stress on the thermal conductivity of dry sand (Wetzel and Rolle), June, 167
Calibration of thermal conductivity sensors for measuring soil suction (Fredlund and Wong), Sept., 188
Tidfors, M. and Sallfors, G.: Temperature effect on preconsolidation pressure, March, 93
Tonthat, A.: *see* Silvestri, V., Karam, G., Tonthat, A., and St-Amour, Y.
Torsional shear apparatus: a cyclic undrained simple shear testing method for soils (Tatsuoka, Pradhan, and Yoshi-ie), Dec., 269
Triaxial equipment: Discussion on "automatic volume change and pressure measurement devices for triaxial testing of soils" by Poul V. Lade (Tatsuoka), Dec., 323
Triaxial tests:
A device for lateral strain measurement in triaxial tests with unsaturated specimens (Kolymbas and Wu), Sept., 227
A nondestructive, specimen-specific method for measurement membrane penetration in the triaxial test (Kramer and Sivaneswaran), March, 50
A nonlinear one-dimensional wave analysis of a triaxial soil specimen (Carroll), March, 45
Horizontal and vertical swell pressures from a triaxial test: feasibility study (Johnson), March, 87
The use of Hall effect semiconductors in geotechnical instrumentation (Clayton, Khatrush, Bica, and Siddique), March, 69
The use of proximity transducers for local strain measurements in triaxial tests (Hird and Yang), 292
The vane cone: a new device for soil shear strength measurement (Youssef), March, 60

U-V

Unconfined compression: Laboratory testing of chemically grouted sand (Christopher, Atmatzidis, and Krizek), June, 109
Unsaturated soils: A device for lateral strain measurements in triaxial tests with unsaturated specimens (Kolymbas and Wu), Sept., 227
Uplift capacity: Enhancement of the uplift capacity of buried pipelines by the use of geogrids (Selvadurai), Sept., 211
Vanes: The vane cone: a new device for soil shear strength measurement (Youssef), March, 60
Void ratio: Effect of rigid boundaries on measurement of particle concentration (Hardin), June, 143
Voids: Pulse shapes from ground penetrating radar (Reames), Sept., 244

W

Wagner, L. A.: *see* Senseny, P. E., Mellegard, K. D., and Wagner, L. A.
Water balloon apparatus: A large-capacity batch filling water balloon apparatus for deep in-situ density tests (Cooper and Fleming), Sept., 222
Wave propagation: A nonlinear one-dimensional wave analysis of a triaxial soil specimen (Carroll), March, 45
Wetzel, R. A. and Rolle, K. C.: A model study of the influence of stress on the thermal conductivity of dry sand, June, 167
Wiesnet, D. R.: *Geotechnical Applications of Remote Sensing and Remote Sensing* by Johnson and Pettersson, March, 102
Williams, D. J.: *see* Sibley, J. W. and Williams, D. J.
Wong, D. K. H.: *see* Fredlund, D. G. and Wong, D. K. H.
Wu, W.: *see* Kolymbas, D. and Wu, W.

X-Y

X-ray radiography: X-ray radiographic investigation of perchloroethylene migration at the Livingston derailment site (Ferrell, Arman, and Grosch), June, 119
Yang, P. C. Y.: *see* Hird, C. C. and Yang, P. C. Y.
Yokel, F. Y.: *see* Ladd, R. S., Dobry, R., Dutko, P., Yokel, F. Y., and Chung, R. M.
Yoshi-ie, H.: *see* Tatsuoka, F., Pradhan, T. B. S., and Yoshi-ie, H.
Youssef, A. -F. A.: The vane cone: a new device for soil shear strength measurement, March, 60